


Phone: 1-800-678-0814 \ 1-503-287-9822 Fax: 1-800-287-7483 \ 1-503-287-7483

# Versa-Steel, Inc.

## Open End Cutting Shoe Data Sheet





#### PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VERSA-STEEL, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VERSA-STEEL, INC. IS PROHIBITED.

#### **Product Description**

Both of our cutting shoes are easy to install with a slip-on fit. The design places the cross-sectional area directly below the wall of the pipe for maximum support during penetration. They are a more heavy duty construction than other brands.

The inside-fit cutting shoe has a weld prep built into the shoe. These tips are designed with a weld chamfer built into the casting. Slip shoe inside pipe and using a 70xx series rod weld a 5/16" or larger weld all around.

Like our inside-fit shoe, this shoe has a slip-on fit, and the cross-sectional area lies below the wall of the pipe. The outside fit cutting shoe has a natural fillet on top for easy welding. These slip fit shoes are easily attached with a 5/16" or larger fillet weld at the top of the flange. For best results, weld all around the shoe with a 70xx series rod.


**Type Inside Fit** 




**Type Outside Fit** 



Versa Steel Open End Cutting Shoe and Pipe Cross-Section View







			DIMENSIONS ARE IN INCHES		NAME	DATE			
			TOLERANCES:	DRAWN	JML	12/27/2007			
			1/X ± 1/16"	CHECKED			Description:		
			.XX ± .01 .XXX ± .003	ENG APPR.			Open End Cutting Shoes		
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VERSA-STEEL, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VERSA-STEEL, INC. IS PROHIBITED.			.XXXX ± .0005	MFG APPR.			Part Number:		
			MATERIAL	Q.A.			ran Number.		
			Steel Alloy	COMMENTS:			]		
	NEXT ASSY	USED ON	FINISH None				SIZE DWG. NQ.  A Equipment Data Sheet A		
	APPLICATION		DO NOT SCALE DRAWING				SCALE:1:5 WEIGHT: SHEET 2 OF 3		

#### **Open End Cutting Shoes**


### Type Inside Fit




These tips are designed with a weld chamfer built into the casting. Slip shoe inside pipe and using a 70xx series rod weld a 5/16" or larger weld all around.



#### Type Outside Fit



These slip fit shoes are easily attached with a 5/16" or larger fillet weld at the top of the flange. For best results, weld all around the shoe with a 70xx series rod.



### PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS

DRAWING IS THE SOLE PROPERTY OF VERSA-STEEL, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VERSA-STEEL, INC. IS PROHIBITED.

		DIMENSIONS ARE IN INCHES		NAME	DATE	
		TOLERANCES:  1/X ± 1/16" .XX ± .01 .XXX ± .003 .XXXX ± .0005  MATERIAL Steel Alloy	DRAWN	JML	12/27/2007	
			CHECKED			[
			ENG APPR.			
			MFG APPR.			
			Q.A.			
			COMMENTS:			
NEXT ASSY	USED ON	FINISH None				
APPLICATION		DO NOT SCALE DRAWING				

#### Description: Open End Cutting Shoes Part Number:

E	<u>w</u> g. 1	vipment Data S	heet	A REV.
ALE:	1:8	WEIGHT:	SHEET 3 OF 3	